



Network UPS 12Vdc. Lithium Battery,19500mAh, BMS, 4LED

CP12142LI

Product availability : Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

1114111	
Main Input Voltage	12 V DC
Product or Component Type	Uninterruptible power supply (UPS)
Main Output Voltage	12 V DC
Kw Rating	38 W
Rated power in VA	140 VA
Battery Type	Li-lon (Lithium Ion)
Provided Equipment	User Manual

Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	24 h

Physical

Width	7.40 in (18.8 cm)
Depth	3.78 in (9.6 cm)
Net Weight	1.65 lb(US) (0.75 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Height	3.78 in (9.6 cm)

Output

Max Configurable Power (Watts) 38 W

Conformance

Standards EN 55022 Class A

Equipment protection policy Lifetime: \$25000

En			

Ambient Air Temperature for Operation	32113 °F (045 °C)
Relative Humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient Air Temperature for Storage	23113 °F (-545 °C)
Storage Relative Humidity	095 % non-condensing
Storage altitude	050000 ft (0.0015240.00 m)

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA	
Discount Schedule	BMS1	
GTIN	731304338741	
Returnability	No	
Country of origin	PH	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.69 in (17 cm)
Package 1 Width	6.10 in (15.5 cm)
Package 1 Length	3.86 in (9.8 cm)
Package 1 Weight	2.25 lb(US) (1.02 kg)
SCC14	10731304338748

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty

2 years repair or replace

Recommended replacement(s)