

# Product data sheet

Specifications



APC Back-UPS Pro 1500VA for Gaming, 120V, Pure Sinewave, LCD, Black, 3 USB charging ports, 10 NEMA outlets (4 surge)

BGM1500B

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	900 W
Rated power in VA	1500 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA
Output connection type	6 NEMA 5-15R 4 NEMA 5-15R surge
Cable length	6 ft (1.83 m)
Number of cables	1
Battery type	Lead-Acid battery

## Batteries & Runtime

Included Battery Modules	0
Typical recharge time	16 h
Battery Charge Power (Watts)	16 W rated
Battery power in VAh	257 VAh capacity 257 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	<a href="#">APCRBC163</a>
Extendable Run Time	0

## General

Provided equipment	Coaxial cable User Manual USB cable
Product web sub-family	Gaming performance
Number of power module free slots	0

---

Number of power module filled slots	0
-------------------------------------	---

---

Redundant	No
-----------	----

---

## Physical

---

Color	Black
-------	-------

---

Height	11.46 in (291 mm)
--------	-------------------

---

Width	4.13 in (105 mm)
-------	------------------

---

Depth	16.06 in (408 mm)
-------	-------------------

---

Net Weight	25.35 lb(US) (11.5 kg)
------------	------------------------

---

Mounting preference	No preference
---------------------	---------------

---

Mounting Mode	Not rack-mountable
---------------	--------------------

---

Two post mountable	0
--------------------	---

---

USB compatible	No
----------------	----

---

## Input

---

Input Frequency	60 Hz +/- 3 Hz
-----------------	----------------

---

Efficiency at full load	88...147 V
-------------------------	------------

---

Maximum Input Current per Phase	12 A
---------------------------------	------

---

Switching current capacity	15 A
----------------------------	------

---

## Output

---

Max Configurable Power (Watts)	900 W
--------------------------------	-------

---

Output Frequency (sync to mains)	60 Hz +/- 3 Hz sync to mains
----------------------------------	------------------------------

---

Topology	Line Interactive
----------	------------------

---

Waveform Type	Sine wave
---------------	-----------

---

Maximum configurable power in VA	1500 VA
----------------------------------	---------

---

## Conformance

---

Product Certifications	ENERGY STAR V2.0 (USA) TUV C-US certified
------------------------	--

---

Equipment protection policy	Lifetime : \$500000
-----------------------------	---------------------

---

## Environmental

---

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

---

Relative Humidity	0...95 % non-condensing
-------------------	-------------------------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
-------------------------------------	--------------------------

---

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

---

Storage altitude	0...10000 ft (0.00...3048.00 m)
------------------	---------------------------------

---

Acoustic level	45 dBA
----------------	--------

---

## Communications & Management

Control panel	Multi-function LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rating	1080 J
Filtering	Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: in
Data line protection	Coaxial cable for CATV/SATV/modem/audio-video

## Ordering and shipping details

GTIN	731304410973
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.46 in (291 mm)
Package 1 Width	16.06 in (408 mm)
Package 1 Length	4.13 in (105 mm)
Package 1 Weight	25.35 lb(US) (11.5 kg)
SCC14	10731304410970

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	3 year repair or replace
----------	--------------------------

## Recommended replacement(s)