

# Product data sheet

Specifications



## APC Back-UPS 1000, Compact Tower, 1000VA, 120V, AVR, LCD, 8 NEMA outlets (4 surge)

BX1000M

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	600 W
Rated power in VA	1000 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA
Output connection type	4 NEMA 5-15R 4 NEMA 5-15R surge
Cable length	6 ft (1.83 m)
Number of cables	1
Battery type	Lead-Acid battery

### Batteries & Runtime

Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	12 h
RBC Quantity	1
Battery Charge Power (Watts)	12 W rated
Battery power in VAh	140 VAh capacity 140 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	<a href="#">APCRBC158</a>
Extendable Run Time	0

### General

Provided equipment	User Manual USB cable
Number of power module free slots	0

---

Number of power module filled slots	0
-------------------------------------	---

---

Redundant	No
-----------	----

---

## Physical

---

Color	Black
-------	-------

---

Height	7.48 in (19 cm)
--------	-----------------

---

Width	3.58 in (9.1 cm)
-------	------------------

---

Depth	12.20 in (31 cm)
-------	------------------

---

Net Weight	15.87 lb(US) (7.2 kg)
------------	-----------------------

---

Mounting preference	No preference
---------------------	---------------

---

Mounting Mode	Not rack-mountable
---------------	--------------------

---

Two post mountable	0
--------------------	---

---

USB compatible	No
----------------	----

---

## Input

---

Input Frequency	60 Hz +/- 3 Hz
-----------------	----------------

---

Efficiency at full load	88...139 V
-------------------------	------------

---

Maximum Input Current per Phase	12 A
---------------------------------	------

---

Switching current capacity	15 A
----------------------------	------

---

## Output

---

Max Configurable Power (Watts)	600 W
--------------------------------	-------

---

Output Frequency (sync to mains)	60 Hz sync to mains
----------------------------------	---------------------

---

Topology	Line Interactive
----------	------------------

---

Waveform Type	Stepped approximation to a sinewave
---------------	-------------------------------------

---

Maximum output current	15 A
------------------------	------

---

Maximum configurable power in VA	1000 VA
----------------------------------	---------

---

Transfer Time	8ms typical : 10 ms maximum
---------------	-----------------------------

---

## Conformance

---

Product Certifications	California (CEC) Battery Charger ENERGY STAR V2.0 (USA) TUV C-US certified
------------------------	--

---

Equipment protection policy	Lifetime : \$250000
-----------------------------	---------------------

---

## Environmental

---

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

---

Relative Humidity	0...95 % non-condensing
-------------------	-------------------------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

---

Storage Relative Humidity	0...95 %
---------------------------	----------

---

Storage altitude	0...50000 ft (0.00...15240.00 m)
------------------	----------------------------------

---

Acoustic level	45 dBA
Heat dissipation	48.5 Btu/h

## Communications & Management

Control panel	Multi-function LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rating	1103 J
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee
Data line protection	Coaxial cable for CATV/SATV/modem/audio-video

## Ordering and shipping details

GTIN	731304331766
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.96 in (25.3 cm)
Package 1 Width	17.40 in (44.2 cm)
Package 1 Length	5.59 in (14.2 cm)
Package 1 Weight	17.64 lb(US) (8 kg)
SCC14	10731304331763

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
ENERGY STAR®	<a href="#">ENERGY STAR UPS V2.0 (USA)</a> <a href="#">↗</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

## Recommended replacement(s)