

Product data sheet

Specifications



APC Back-UPS 1350, Compact Tower, 1350VA, 120V, AVR, LCD, 10 NEMA outlets (5 surge)

BX1350M

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	810 W
Rated power in VA	1350 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA
Output connection type	5 NEMA 5-15R 5 NEMA 5-15R surge
Cable length	6 ft (1.83 m)
Number of cables	1
Battery type	Lead-Acid battery

Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	16 h
RBC Quantity	1
Battery Charge Power (Watts)	9 W rated
Battery power in VAH	150 VAh capacity 150 VAh runtime
Extendable Run Time	0
Replacement battery	APCRBC123

General

Provided equipment User Manual
USB cable

Number of power module free slots 0

Number of power module filled slots	0
-------------------------------------	---

Redundant	No
-----------	----

Physical

Height	9.84 in (25 cm)
--------	-----------------

Width	3.94 in (10 cm)
-------	-----------------

Depth	15.04 in (38.2 cm)
-------	--------------------

Net Weight	22.49 lb(US) (10.2 kg)
------------	------------------------

Mounting preference	No preference
---------------------	---------------

Mounting Mode	Not rack-mountable
---------------	--------------------

Two post mountable	0
--------------------	---

USB compatible	No
----------------	----

Input

Input Frequency	60 Hz +/- 3 Hz
-----------------	----------------

Efficiency at full load	88...139 V
-------------------------	------------

Maximum Input Current per Phase	12 A
---------------------------------	------

Switching current capacity	15 A
----------------------------	------

Output

Max Configurable Power (Watts)	810 W
--------------------------------	-------

Output Frequency (sync to mains)	60 Hz sync to mains
----------------------------------	---------------------

Topology	Line Interactive
----------	------------------

Waveform Type	Stepped approximation to a sinewave
---------------	-------------------------------------

Maximum configurable power in VA	1350 VA
----------------------------------	---------

Transfer Time	8ms typical : 10 ms maximum
---------------	-----------------------------

Conformance

Product Certifications	California (CEC) Battery Charger ENERGY STAR V2.0 (USA) TUV C-US certified
------------------------	--

Equipment protection policy	Lifetime : \$250000
-----------------------------	---------------------

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Relative Humidity	0...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0...50000 ft (0.00...15240.00 m)
------------------	----------------------------------

Acoustic level	45 dBA
----------------	--------

Heat dissipation	67.6 Btu/h
------------------	------------

Communications & Management

Control panel	Multi-function LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	789 J
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee
Data line protection	Coaxial cable for CATV/SATV/modem/audio-video


Ordering and shipping details

GTIN	731304331773
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.70 in (34.8 cm)
Package 1 Width	19.33 in (49.1 cm)
Package 1 Length	8.94 in (22.7 cm)
Package 1 Weight	26.24 lb(US) (11.9 kg)
SCC14	10731304331770

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA) 
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Recommended replacement(s)