

Product data sheet

Specifications



Easy UPS 3S Modular Battery Cabinet, 208V

E3SXR7

Overview

Presentation	Modular battery cabinet for extended runtime for UPSs with internal batteries. The cabinet is supplied without batteries, so batteries must be purchased separately.
Lead time	Usually Ships within 2 Weeks

Main

Battery Type	VRLA
Provided Equipment	Installation guide

Batteries & Runtime

Device mounting	Enclosed battery cabinet
------------------------	--------------------------

Physical

Color	White
Height	55.12 in (140 cm)
Width	19.69 in (50 cm)
Depth	37.01 in (94 cm)
Net Weight	352.74 lb(US) (160 kg)

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...6561.68 ft (0...2000 m)
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Storage Relative Humidity	0...95 % non-condensing

Ordering and shipping details

GTIN	731304427582
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
Package 1 Height	62.80 in (1595 mm)
Package 1 Width	47.24 in (1200 mm)
Package 1 Length	31.50 in (800 mm)
Package 1 Weight	379.20 lb(US) (172 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
RoHS exemption information	Yes

Recommended replacement(s)