# Parallel Maintenance Bypass Panel for 2 UPSs, 60-120kW 400V wallmount for Galaxy VS & Easy UPS 3S/3M

GVSBPAR60K120H

|  | ew |
|--|----|
|  |    |

| Presentation | Maintenance bypass panel for complete isolation of two UPSs in parallel during service operations. |
|--------------|--|
| Lead time    | Usually Ships within 2 Weeks   |

### **Physical**

| Height     | 39.37 in (100 cm)     |
|------------|-----------------------|
| Width      | 35.43 in (90 cm)      |
| Depth      | 11.02 in (28 cm)      |
| Net Weight | 182.98 lb(US) (83 kg) |

#### **Environmental**

| Ambient Air Temperature for<br>Operation | 32104 °F (040 °C)    |
|--|----------------------|
| Ambient Air Temperature for Storage      | -13131 °F (-2555 °C) |

# Ordering and shipping details

| GTIN | 731304367383 |  |
|------|--------------|--|

## **Packing Units**

| Unit Type of Package 1       | PCE                    |
|------------------------------|------------------------|
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 22.24 in (56.5 cm)     |
| Package 1 Width              | 47.24 in (120 cm)      |
| Package 1 Length             | 39.37 in (100 cm)      |
| Package 1 Weight             | 249.12 lb(US) (113 kg) |

## Offer Sustainability

| Sustainable offer status | Green Premium product         |
|--------------------------|-------------------------------|
| REACh Regulation         | REACh Declaration             |
| EU RoHS Directive        | Compliant EU RoHS Declaration |
| Mercury free             | Yes                           |

| RoHS exemption information  | Yes                           |
|-----------------------------|-------------------------------|
| Environmental Disclosure    | Product Environmental Profile |
| Circularity Profile         | End of Life Information       |
| Optimized Energy Efficiency | Energy efficient product      |
| Take-back                   | Take-back program available   |

Recommended replacement(s)