Product data sheet

Specifications



Maintenance Bypass Panel, single unit, 150kW 400V wallmount, for Galaxy VS and Easy UPS 3M

GVSBPSU150KH

O				

Presentation	Maintenance bypass cabinet for complete isolation of the UPS during service operations.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage 400 V 3 phase

Physical

Height	31.50 in (80 cm)
Width	23.62 in (60 cm)
Depth	11.02 in (28 cm)
Net Weight	105.82 lb(US) (48 kg)

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Operating altitude	03000 ft
Relative Humidity	095 % non-condensing
Ambient Air Temperature for Storage	-13131 °F (-2555 °C)
Storage Relative Humidity	095 % non-condensing

Ordering and shipping details

GTIN 731304405658

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.29 in (49 cm)
Package 1 Width	33.07 in (84 cm)
Package 1 Length	48.03 in (122 cm)
Package 1 Weight	132.28 lb(US) (60 kg)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Recommended replacement(s)