

Product data sheet

Specifications



Galaxy VM Level 2 Seismic Kit for Narrow Modular Battery Cabinet

GVML2MBCN-KIT

Overview

Presentation	Kit includes parts and fasteners to achieve Seismic level 2 certification
Lead time	Usually in Stock

Physical

Height	4.17 in (10.6 cm)
Width	14.57 in (37 cm)
Depth	32.17 in (81.7 cm)
Net Weight	37.48 lb(US) (17 kg)

Conformance

Product Certifications	C-tick RCM
Standards	EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 UL 1778

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...3333 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage altitude	0...49212 ft (0.00...14999.82 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	731304320777
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.99 in (20.3 cm)

Package 1 Width	34.02 in (86.4 cm)
Package 1 Length	15.98 in (40.6 cm)
Package 1 Weight	39.99 lb(US) (18.14 kg)

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------

Recommended replacement(s)