Product data sheet

Specifications



Galaxy VM UPS Modular Battery Cabinet wide up to 12 strings

GVMMODBCW

Overview

Presentation	Wide modular battery cabinet with up to a 12 string modular battery capacity. To be used with GVMMBTU battery string. Batteries are not included in the SKU and must be purchased separately.

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage	480 V 3 phase
Battery type	VRLA
Provided Equipment	Installation guide

Batteries & Runtime

Battery Placement	Battery Cabinet
Battery Slots Empty	12
Included Battery Modules	0
Device mounting	Enclosed battery cabinet
Battery voltage	480V

Physical

Color	White
Height	77.56 in (197 cm)
Width	27.56 in (70 cm)
Depth	33.62 in (85.4 cm)
Net Weight	462.97 lb(US) (210 kg)

Input

Input Frequency 40 - 70 Hz

Conformance

Standards FCC Part 15 class A OSHPD

EN/IEC 62040-3 UL 1778

Environmental

Ambient air temperature for operation	32104 °F (040 °C)
Operating altitude	03333 ft
Relative Humidity	095 %
Ambient Air Temperature for Storage	5104 °F (-1540 °C)
Storage altitude	049212 ft (0.0014999.82 m)
Storage Relative Humidity	095 %

Ordering and shipping details

GTIN	731304311263

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.65 in (215 cm)
Package 1 Width	41.73 in (106 cm)
Package 1 Length	38.98 in (99 cm)
Package 1 Weight	555.57 lb(US) (252 kg)

Offer Sustainability

Offer Sustainability	
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
Compliant EU RoHS Declaration	
Yes	
Yes	
Product Environmental Profile	
End of Life Information	
Energy efficient product	
Take-back program available	

Contractual warranty

Recommended replacement(s)