

# Product data sheet

Specifications



## Galaxy VM System Bypass Cabinet 675K 480V

GVMSBC675KG

### Overview

<b>Presentation</b>	System bypass cabinet for use in a parallel configuration with up to a 675kVA maximum load capacity.
<b>Lead time</b>	Usually Ships within 2 Weeks

### Main

<b>Main Input Voltage</b>	480 V 3 phase
<b>Main Output Voltage</b>	480 V 3 phase
<b>Output connector type</b>	Hard Wire 4-wire (3PH + G) 1 Hard Wire 5-wire (3PH + N + G) 1
<b>Provided Equipment</b>	Installation guide

### Physical

<b>Color</b>	White
<b>Height</b>	77.56 in (197 cm)
<b>Width</b>	59.25 in (150.5 cm)
<b>Depth</b>	32.95 in (83.7 cm)
<b>Net Weight</b>	1113.34 lb(US) (505 kg)
<b>Mounting Support</b>	Floor
<b>USB compatible</b>	No

### Input

<b>Input Frequency</b>	50/60 Hz
------------------------	----------

### Conformance

<b>Product Certifications</b>	cUL Listed
<b>Standards</b>	EN/IEC 62040-3 FCC Part 15 class A FCC Part 15 class B OSHDP UL 1778

### Environmental

<b>Ambient air temperature for operation</b>	32...104 °F (0...40 °C)
<b>Relative Humidity</b>	0...95 %

Operating altitude	0...3333 ft
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...49212 ft (0.00...14999.82 m)

## Ordering and shipping details

GTIN	731304311287
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80.55 in (204.6 cm)
Package 1 Width	45.51 in (115.6 cm)
Package 1 Length	71.06 in (180.5 cm)
Package 1 Weight	1278.99 lb(US) (580.14 kg)

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	-------------------------------------------------------------------

## Recommended replacement(s)