

Product data sheet

Specifications



Galaxy VM System Bypass Cabinet 675K 480V with load bank breaker

GVMSBCLB675KG

Overview

Presentation	System bypass cabinet used in a parallel configuration with a maximum load capacity of 675 kVA. Load bank breaker is included.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	480 V 3 phase
Main Output Voltage	480 V 3 phase
Output connector type	Hard Wire 4-wire (3PH + G) 1 Hard Wire 5-wire (3PH + N + G) 1
Provided Equipment	Installation guide

Physical

Color	White
Height	77.56 in (197 cm)
Width	70.28 in (178.5 cm)
Depth	32.95 in (83.7 cm)
Net Weight	1289.71 lb(US) (585 kg)

Input

Input Frequency	40 - 70 Hz
------------------------	------------

Conformance

Standards	EN/IEC 62040-3 FCC Part 15 class A FCC Part 15 class B OSH PD UL 1778
------------------	---

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...3333 ft
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)

Storage Relative Humidity	0...95 %
Storage altitude	0...49212 ft (0.00...14999.82 m)

Ordering and shipping details

GTIN	731304311294
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80.55 in (204.6 cm)
Package 1 Width	45.51 in (115.6 cm)
Package 1 Length	82.09 in (208.5 cm)
Package 1 Weight	1488.12 lb(US) (675 kg)

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Recommended replacement(s)