



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>

## NTE1026 Integrated Circuit Module, Hybrid OSC/Buffer

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Maximum Supply Voltage, $V_{CCmax}$ .....	-20V
Operating Current .....	40mA
Maximum Power Dissipation, $P_d$ .....	100mW
Operating Temperature Range, $T_{opr}$ .....	-20° to +80°C
Storage Temperature Range, $T_{stg}$ .....	-20° to +100°C

**Recommended Operating Conditions:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Supply Voltage, $V_{CC}$ .....	-15V
--------------------------------	------

**Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Oscillation Voltage	$V_{OSC}$	$V_{CC} = -15V$	13	14	-	V
Oscillation Frequency	$f_{OSC}$		-	1.8	-	kHz

