

Hinged Wall Mount Brackets

KEY FEATURES

- EIA/ECA-310-E 19-in mounting standard
- 6-inch standoff depth
- Cable access holes, rear and sides
- Right- or left-hand swing
- 16-gauge steel, black polyurethane finish



Hinged Wall Mount Brackets are designed for mounting one or more 19-inch panels and have a 6-inch standoff depth. Brackets are constructed from 16-gauge steel with a black polyurethane finish. Brackets have cable access holes on both the rear and sides of the brackets to allow a variety of cable access configurations. Brackets can be mounted for either right or left hand swing.

Product Title	
PART NUMBER	DESCRIPTION
HWB-175	1-RMS Hinged Wall Mount Bracket, 1.75" H x 19" W x 6" D
HWB-350	2-RMS Hinged Wall Mount Bracket, 3.50"H x 19" W x 6"D
HWB-525	3-RMS Hinged Wall Mount Bracket, 5.25"H x 19" W x 6"D
HWB-700	4-RMS Hinged Wall Mount Bracket, 7.00"H x 19" W x 6"D
HWB-875	5-RMS Hinged Wall Mount Bracket, 8.75"H x 19" W x 6"D

SPECIFICATIONS

Manufacturer: Signamax

Material: Steel

Mounting Type: Wall

Product Type: Simple

Unit of Measure: EA

ENVIRONMENTAL CONDITIONS

Operating Temperature: -10 °C +60 °C (+14 °F +140 °F)

Storage Temperature: -40 °C +70 °C (-40 °F +158 °F)

Operating RH: max non-condensing 93 %

WARRANTY

5-year limited component warranty