

Product data sheet

Specifications



APC Smart-UPS SRT 192V 5kVA and 6kVA RM Battery Pack



SRT192RMBP

Overview

Lead time Usually in Stock

Main

Number of rack unit 3U
Battery type Lead-Acid battery
Provided Equipment Installation guide
Warranty card

Batteries & Runtime

Battery Slots Empty 0
Included Battery Modules 0
Device mounting Stand alone battery stack
Battery voltage 192V
RBC Quantity 2
Replacement battery [APCRBC140](#)

Physical

Color Black
Height 5.12 in (13 cm)
Width 17.01 in (43.2 cm)
Depth 26.88 in (68.27 cm)
Net Weight 200.62 lb(US) (91 kg)
Mounting Mode Rack-mounted

Conformance

Standards OSHPD

Environmental

Ambient air temperature for operation 32...104 °F (0...40 °C)
Operating altitude 0...10000 ft

| | |
|-------------------------------------|----------------------------------|
| Relative Humidity | 0...95 % non-condensing |
| Ambient Air Temperature for Storage | 5...113 °F (-15...45 °C) |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |
| Storage Relative Humidity | 0...95 % non-condensing |

Ordering and shipping details

| | |
|------|--------------|
| GTIN | 731304301776 |
|------|--------------|

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 16.54 in (42 cm) |
| Package 1 Width | 23.62 in (60 cm) |
| Package 1 Length | 39.37 in (100 cm) |
| Package 1 Weight | 232.59 lb(US) (105.5 kg) |

Offer Sustainability

| | |
|---------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Recommended replacement(s)