

Product data sheet

Specifications



APC Smart-UPS On-Line, 1000VA, Rackmount 2U, 120V, 6x 5-15R NEMA outlets, Network Card, Extended runtime, W/ rail kit

SRT1000RMXLA-NC

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V

Main Output Voltage 120 V

Kw Rating 900 W

Rated power in VA 1000 VA

Input Connection Type NEMA 5-15P

Output connection type 6 NEMA 5-15R

Number of rack unit 2U

Cable length 6 ft (1.83 m)

Number of cables 1

Battery type Lead-Acid battery

Provided equipment
CD with software
Documentation CD
Installation guide
Network Management Card
Rack mounting hardware
Rack Mounting brackets
Rack Mounting support rails
Temperature Probe
USB cable
Warranty card

Batteries & Runtime

Included Battery Modules 1

Battery Slots Empty 0

Typical recharge time 3 h

RBC Quantity 1

Battery voltage 48V

Battery Charge Power (Watts) 102 W rated

Battery power in VAH 306 VAh runtime

Battery Life 3...5 year(s)

Replacement battery [APCRBC155](#)

Battery option	SRT48RMBP 1 890 VAh SRT48RMBP 2 1484 VAh SRT48RMBP 3 2078 VAh SRT48RMBP 4 2671 VAh SRT48RMBP 5 3265 VAh SRT48RMBP 6 3859 VAh SRT48RMBP 8 5047 VAh SRT48RMBP 10 6233 VAh
-----------------------	--

Extendable Run Time	1
----------------------------	---

General

Product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Color	Black
Height	3.35 in (8.5 cm)
Width	17.01 in (43.2 cm)
Depth	20.00 in (50.8 cm)
Net Weight	48.50 lb(US) (22 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

Input

Input Frequency	40 - 70 Hz auto-sensing
Efficiency at full load	50...150 V 40% load 80...150 V

Output

Max Configurable Power (Watts)	900 W
Harmonic distortion	Less than 2%
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
Topology	Double Conversion Online
Waveform Type	Sine wave
Bypass type	Built-in Static Bypass
Maximum configurable power in VA	1000 VA

Conformance

Product Certifications	ENERGY STAR V2.0 (USA)
-------------------------------	------------------------

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-4...122 °F (-20...50 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	50 dBA
Heat dissipation	317 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	432 J
---------------------	-------


Ordering and shipping details

GTIN	731304329978
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.69 in (24.6 cm)
Package 1 Width	29.49 in (74.9 cm)
Package 1 Length	23.39 in (59.4 cm)
Package 1 Weight	65.26 lb(US) (29.6 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA) 
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Optimized Energy Efficiency	Energy efficient product
------------------------------------	--------------------------

Take-back	Take-back program available
------------------	-----------------------------

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

Recommended replacement(s)