

# Product data sheet

Specifications



## APC Smart-UPS On-Line, 3kVA, Tower, 120V, 8x 5-20R+1x L5-30R NEMA outlets, SmartSlot, Extended runtime, W/O rail kit

SRT3000XLA

### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	2700 W
Rated power in VA	3000 VA
Input Connection Type	NEMA L5-30P
Output connection type	8 NEMA 5-20R 1 NEMA L5-30R
Cable length	10 ft (3.05 m)
Number of cables	1
Battery type	Lead-Acid battery
Provided equipment	CD with software Documentation CD Installation guide Removable support feet USB cable Warranty card

### Batteries & Runtime

Included Battery Modules	1
Typical recharge time	3 h
RBC Quantity	1
Battery voltage	96V
Battery Charge Power (Watts)	151 W rated
Battery power in VAh	454 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	<a href="#">APCRBC152</a>
Battery option	SRT96BP 1 1362 VAh SRT96BP 2 2270 VAh SRT96BP 3 3178 VAh SRT96BP 4 4086 VAh SRT96BP 5 4994 VAh SRT96BP 6 5902 VAh

Extendable Run Time 1

## General

Product web sub-family High density

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

## Physical

Color Black

Height 17.01 in (43.2 cm)

Width 3.35 in (8.5 cm)

Depth 25.00 in (63.5 cm)

Net Weight 69.00 lb(US) (31.3 kg)

Mounting Location Front

Mounting preference Lower

Mounting Mode Not rack-mountable

Two post mountable 0

USB compatible Yes

Mounting position Vertical

## Input

Input Frequency 40 - 70 Hz auto-sensing

## Output

Max Configurable Power (Watts) 2700 W

Harmonic distortion Less than 2%

Output Frequency (sync to mains) 50/60 Hz +/- 3 Hz sync to mains

Crest factor 3 : 1

Topology Double Conversion Online

Waveform Type Sine wave

Bypass type Internal Bypass (Automatic and Manual)

Maximum configurable power in VA 3000 VA

## Conformance

Product Certifications ENERGY STAR V2.0 (USA)

## Environmental

Ambient air temperature for operation 32...104 °F (0...40 °C)

Relative Humidity 0...95 % non-condensing

Operating altitude 0...10000 ft

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	55 dBA
Heat dissipation	805 Btu/h
IP degree of protection	IP20

## Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

## Surge Protection and Filtering

Surge energy rating	340 J
---------------------	-------


## Ordering and shipping details

GTIN	731304325185
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.69 in (24.6 cm)
Package 1 Width	34.29 in (87.1 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	81.00 lb(US) (36.74 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
ENERGY STAR®	<a href="#">ENERGY STAR UPS V2.0 (USA)</a> 
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

## Recommended replacement(s)