

Product data sheet

Specifications



APC Smart-UPS On-Line, 3kVA,
Lithium-ion, Rackmount 1U, 120V,
5x 5-20R + 1x L5-30R NEMA
outlets, Network Card, Extended
runtime, W/ rail kit

SRTL3KRM1UNC

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V 125 V
Product or Component Type	Uninterruptible power supply (UPS)
Other Input Voltage	120 V 125 V
Main Output Voltage	120 V
Other Output Voltage	120 V 125 V
Kw Rating	2880 W
Rated power in VA	2880 VA
Input Connection Type	NEMA L5-30P
Output connection type	5 NEMA 5-20R 1 NEMA L5-30R
Number of rack unit	1U
Cable length	8 ft (2.44 m)
Number of cables	1
Battery type	Li-Ion (Lithium Ion)
Provided equipment	RJ45 Cable USB cable Country-specific detachable power cord Rack Mounting brackets Rack Mounting support rails Installation guide Warranty card

Batteries & Runtime

Typical recharge time	1.5 h
Battery voltage	50 V
Battery Charge Power (Watts)	448 W
Battery power in VAH	312 VAh runtime
Battery option	SRTL50RMBP1U-LI 1 1452 VAh SRTL50RMBP1U-LI 2 2592 VAh SRTL50RMBP1U-LI 3 3732 VAh

Extendable Run Time 1

General

Redundant No

Physical

Color Silver grey

Height 1.69 in (43 mm)

Width 17.01 in (432 mm)

Depth 22.05 in (560 mm)

Net Weight 35.05 lb(US) (15.9 kg)

Mounting preference No preference

Mounting Mode Rack-mounted with kit
Tower-mounted with kit

Two post mountable 1

USB compatible Yes

Input

Input Frequency 50/60 Hz

Output

Max Configurable Power (Watts) 2880 W

Output Frequency (sync to mains) 50/60 Hz +/- 3 Hz sync to mains

Crest factor 3 : 1

Topology On-Line

Waveform Type Sine wave

Bypass type Internal Bypass (Automatic and Manual)

Maximum configurable power in VA 2880 VA

Conformance

Product Certifications UL/cUL listed
FCC

Standards UL 1778
CSA C22.2 No.107.3-05
FCC Part 15 class A

Environmental

Ambient air temperature for operation 32...104 °F (0...40 °C)

Relative Humidity 0...95 % non-condensing

Operating altitude 0...10000 ft

Ambient Air Temperature for Storage 5...113 °F (-15...45 °C)

Storage Relative Humidity 0...95 % non-condensing

Storage altitude 0...50000 ft (0.00...15240.00 m)

Acoustic level 55 dB

IP degree of protection	IP20
-------------------------	------

Communications & Management

Control panel	Multi-function LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

Ordering and shipping details

GTIN	731304435549
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.95 in (278.2 mm)
Package 1 Width	22.20 in (564 mm)
Package 1 Length	30.08 in (764 mm)
Package 1 Weight	53.3 lb(US) (24.18 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
RoHS exemption information	Yes

Contractual warranty

Warranty	5 years repair or replace
----------	---------------------------

Recommended replacement(s)