

# Product data sheet

Specifications



## APC Smart-UPS, Line Interactive, 1000VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT1000RM2UC

### Overview

<b>Presentation</b>	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
<b>Lead time</b>	Usually Ships within 2 Weeks

### Main


<b>Main Input Voltage</b>	120 V
<b>Other Input Voltage</b>	110 V 125 V
<b>Main Output Voltage</b>	120 V
<b>Other Output Voltage</b>	110 V 125 V
<b>Kw Rating</b>	700 W
<b>Rated power in VA</b>	1000 VA
<b>Input Connection Type</b>	NEMA 5-15P
<b>Output connection type</b>	6 NEMA 5-15R
<b>Number of rack unit</b>	2U
<b>Cable length</b>	8 ft (2.44 m)
<b>Number of cables</b>	1
<b>Battery type</b>	Lead-Acid battery
<b>Provided equipment</b>	Documentation CD Installation guide Rack Mounting support rails Smart UPS signalling RS-232 cable USB cable

### Complementary

<b>Software package</b>	SmartConnect software for remote power monitoring feature availability varies by terms of use
-------------------------	---

### Batteries & Runtime

<b>Extendable Run Time</b>	0
<b>Included Battery Modules</b>	0
<b>Battery Slots Empty</b>	0
<b>Typical recharge time</b>	3 h
<b>RBC Quantity</b>	1

Battery Life	4...6 year(s)
Replacement battery	<a href="#">APCRBC157</a> 
Battery power in VAH	336 VAh runtime
Battery Charge Power (Watts)	112 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	Cloud-enabled monitoring
Redundant	No

## Physical

Color	Black
Height	3.39 in (8.6 cm)
Width	17.01 in (43.2 cm)
Depth	18.78 in (47.7 cm)
Net Weight	55.78 lb(US) (25.3 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

## Input

Efficiency at full load	75...154 V adjustable 82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Crest factor	3 : 1
Harmonic distortion	Less than 5%
Maximum configurable power in VA	1000 VA
Max Configurable Power (Watts)	700 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product Certifications	cULus ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$150000

## Environmental

Acoustic level	41 dBA
Heat dissipation	175 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control panel	Multi-function LCD status and control console
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m


## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304322788
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.25 in (23.5 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	23.23 in (59 cm)
Package 1 Weight	68.17 lb(US) (30.92 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
ENERGY STAR®	<a href="#">ENERGY STAR UPS V2.0 (USA)</a> 
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

---

<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>Optimized Energy Efficiency</b>	Energy efficient product
<b>Take-back</b>	Take-back program available

---

## **Contractual warranty**

---

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

**Dimensions**

---



SMT1000RM2UC

**Recommended replacement(s)**