

Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1500VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD, TAA

SMT1500RM2UCUS

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V

Other Input Voltage 120 V

Main Output Voltage 120 V

Other Output Voltage 120 V

Input Connection Type NEMA 5-15P

Output connection type 6 NEMA 5-15R

Provided equipment CD with software

Batteries & Runtime

Battery power in VAh 432 VAh runtime

Battery Charge Power (Watts) 144 W rated

Physical

Color Black

Input

Efficiency at full load 75...154 V adjustable

Input Frequency 50/60 Hz +/- 3 Hz auto-sensing

Output

Output Frequency (sync to mains) 50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications ENERGY STAR V2.0 (USA)

Environmental

Relative Humidity 0...95 %

Storage Relative Humidity 0...95 %

Ordering and shipping details

GTIN 731304424420

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.25 in (23.5 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	23.23 in (59 cm)
Package 1 Weight	70.81 lb(US) (32.12 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 3 Years

Recommended replacement(s)