Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 750VA, Tower, 120V, 6x NEMA 5-15R outlets, SmartConnect Port +SmartSlot, AVR, LCD, TAA

SMT750CUS

_			
()	VA	r\/I	ew
v	VC	1 V I	

Lead time	Usually in Stock

Main	
Main Input Voltage	120 V
Main Output Voltage	120 V
Input Connection Type	NEMA 5-15P
Output connection type	6 NEMA 5-15R
Provided equipment	CD with software

Batteries & Runtime

Battery power in VAH	146 VAh runtime
Battery Charge Power (Watts)	49 W rated

Physical

Color Black	
--------------------	--

Input

Efficiency at full load	75154 V adjustable
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Output Frequency (sync to	50/60 Hz +/- 3 Hz sync to mains
mains)	

Conformance

Product Certifications	ENERGY STAR V2.0 (USA)
------------------------	------------------------

Environmental

Relative Humidity	095 %
Storage Relative Humidity	095 %

Ordering and shipping details

GTIN 731304424406

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
RoHS exemption information	Yes

Contractual warranty

Warranty 3 Years

Recommended replacement(s)