

Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 750VA, Lithium-ion, Rack/Tower, 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, Short Depth, AVR, LCD

SMTL750RM2UC

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Other Input Voltage	110 V 125 V
Main Output Voltage	120 V
Other Output Voltage	110 V 125 V
Kw Rating	600 W
Rated power in VA	750 VA
Input Connection Type	NEMA 5-15P
Output connection type	6 NEMA 5-15R
Number of rack unit	2U
Cable length	8 ft (2.44 m)
Battery type	Li-Ion (Lithium Ion)
Provided equipment	Installation guide Documentation CD Rack Mounting support rails Smart UPS signalling RS-232 cable USB cable

Complementary

Software package SmartConnect software for remote power monitoring feature availability varies by terms of use

Batteries & Runtime

Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0
Typical recharge time	3 h
Battery design life	8...10 year(s)
Battery power in VAh	86 VAh runtime

Battery Charge Power (Watts)	50 W rated
------------------------------	------------

General

Product web sub-family	Cloud-enabled monitoring
------------------------	--------------------------

Redundant	No
-----------	----

Physical

Color	Black with silver front bezel
-------	-------------------------------

Height	3.39 in (8.6 cm)
--------	------------------

Width	17.24 in (43.8 cm)
-------	--------------------

Depth	12.52 in (31.8 cm)
-------	--------------------

Net Weight	34.00 lb(US) (15.42 kg)
------------	-------------------------

Mounting preference	Lower
---------------------	-------

Mounting Mode	Rack-mounted
---------------	--------------

USB compatible	Yes
----------------	-----

Input

Input protection type	Circuit breaker
-----------------------	-----------------

Efficiency at full load	75...154 V adjustable 82...144 V
-------------------------	-------------------------------------

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
-----------------	--------------------------------

Output

Crest factor	3 : 1
--------------	-------

Harmonic distortion	Less than 5%
---------------------	--------------

Maximum configurable power in VA	750 VA
----------------------------------	--------

Max Configurable Power (Watts)	600 W
--------------------------------	-------

Transfer Time	6ms typical : 10ms maximum
---------------	----------------------------

Topology	Line Interactive
----------	------------------

Waveform Type	Sine wave
---------------	-----------

Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
----------------------------------	---------------------------------

Conformance

Product Certifications	NOM
------------------------	-----

Equipment protection policy	Lifetime : \$150000
-----------------------------	---------------------

Environmental

Acoustic level	41 dBA
----------------	--------

Heat dissipation	135 Btu/h
------------------	-----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Ambient Air Temperature for Storage	-40...95 °F (-40...35 °C)
-------------------------------------	---------------------------

Storage altitude	0...25000 ft (0.00...7620.00 m)
------------------	---------------------------------

IP degree of protection	IP20
Relative Humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

Communications & Management

Alarm	Audible and visible alarms
Control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Yes
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

GTIN	731304341994
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.02 in (22.9 cm)
Package 1 Width	18.58 in (47.2 cm)
Package 1 Length	22.99 in (58.4 cm)
Package 1 Weight	39.00 lb(US) (17.69 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Recommended replacement(s)