

# Product data sheet

Specifications



## APC Smart-UPS X, Line Interactive, 1000VA, Rack/tower convertible 2U, 120V, 8x 5-15R NEMA, SmartConnect port+NMC, Extended runtime

SMX1000CNC

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage 120 V AC 1 phase

Other Input Voltage 120 V

Main Output Voltage 120 V

Other Output Voltage 120 V

Kw Rating 900 W

Rated power in VA 1000 VA

Input Connection Type NEMA 5-15P

Output connection type 8 NEMA 5-15R

Number of rack unit 2U

Cable length 8 ft (2.44 m)

Number of cables 1

Battery type Lead-Acid battery

Provided equipment  
Installation guide  
Rack Mounting brackets  
Removable support feet  
Smart UPS signalling RS-232 cable  
USB cable  
Cat 5 ethernet cable

### Complementary

Software package SmartConnect software for remote power monitoring feature availability varies by terms of use

### Batteries & Runtime

Battery voltage 48V


Extendable Run Time 1

Battery Capacity 345 Ah

Included Battery Modules 0

Battery Slots Empty 0

Typical recharge time 3 h

RBC Quantity	1
Overcurrent protection	60 A
Battery Life	3...5 year(s)
Replacement battery	<a href="#">APCRBC116</a> 
Battery power in VAH	257 VAh runtime
Battery Charge Power (Watts)	99 W rated
Battery option	SMX48RMBP2U 1 939 VAh SMX48RMBP2U 2 1624 VAh SMX48RMBP2U 3 2304 VAh SMX48RMBP2U 4 3000 VAh SMX48RMBP2U 5 3672 VAh

## General

Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	Extended run Network card pre-installed
Redundant	No

## Physical

Color	Black
Height	17.01 in (43.2 cm)
Width	3.50 in (8.9 cm)
Depth	19.29 in (49 cm)
Net Weight	50.40 lb(US) (22.86 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted with kit
Two post mountable	1
USB compatible	Yes
Mounting position	Horizontal Vertical

## Input

Maximum Input Current per Phase	12 A
Input protection type	Circuit breaker
Switching current capacity	15 A
Plug standard	5-15P
Efficiency at full load	82...143 V AC
Input current	8.33 mA rated
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Crest factor	3 : 1
Harmonic distortion	Less than 5%

Maximum configurable power in VA	1000 VA
Max Configurable Power (Watts)	900 W
Output voltage tolerance	+/- 2%
Topology	Line Interactive
Waveform Type	Sine wave
Full load runtime	00:07:15 900 W
Half load runtime	00:19:48 450 W
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product Certifications	ENERGY STAR V2.0 (USA) cUL Listed
Equipment protection policy	Lifetime : \$150000
Marking	CULus FCC

## Environmental

Acoustic level	40 dB
Heat dissipation	117 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
IP degree of protection	IP20
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Yes
Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rating	693 J
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee

## Ordering and shipping details

GTIN	731304428114
------	--------------

## Packing Units

Unit Type of Package 1	PCE
------------------------	-----

<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	23.19 in (58.9 cm)
<b>Package 1 Width</b>	24.41 in (62 cm)
<b>Package 1 Length</b>	9.69 in (24.6 cm)
<b>Package 1 Weight</b>	60.23 lb(US) (27.32 kg)
<b>SCC14</b>	10731304428111

## Offer Sustainability

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

<b>Warranty</b>	3 years repair or replace for hardware. 2 years for battery, plus 1 additional year if customers registers device to SmartConnect
-----------------	---

## Recommended replacement(s)