

Product data sheet

Specifications



APC Smart-UPS X, Line Interactive,
1000VA, Rack/tower convertible
2U, 120V, 8x 5-15R NEMA,
SmartConnect port, Extended
runtime, TAA

SMX1000CUS

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V
Main Output Voltage 120 V
Input Connection Type NEMA 5-15P
Output connection type 8 NEMA 5-15R
Provided equipment CD with software

Batteries & Runtime

Battery power in VAh 257 VAh runtime
Battery Charge Power (Watts) 99 W rated
Battery option SMX48RMBP2U 5 888 VAh

Physical

Color Black

Input

Efficiency at full load 75...154 V adjustable
Input Frequency 50/60 Hz +/- 3 Hz auto-sensing

Output

Output Frequency (sync to mains) 50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications ENERGY STAR V2.0 (USA)

Environmental

Relative Humidity 0...95 %
Storage Relative Humidity 0...95 %

Ordering and shipping details

GTIN 731304424444

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Offer Sustainability

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

RoHS exemption information [Yes](#)

WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 3 Years

Recommended replacement(s)