

# Product data sheet

Specifications



APC Smart-UPS X, Line Interactive, 1500VA, Rack/tower convertible 2U, 120V, 8x 5-15R NEMA, SmartConnect port, Extended runtime, TAA

SMX1500RM2UCUS

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage 120 V  
Main Output Voltage 120 V  
Input Connection Type NEMA 5-15P  
Output connection type 8 NEMA 5-15R  
Provided equipment CD with software

## Batteries & Runtime

Battery power in VAh 288 VAh runtime  
Battery Charge Power (Watts) 103 W rated  
Battery option SMX48RMBP2U 5 939 VAh

## Physical

Color Black

## Input

Efficiency at full load 75...154 V adjustable  
Input Frequency 50/60 Hz +/- 3 Hz auto-sensing

## Output

Output Frequency (sync to mains) 50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product Certifications ENERGY STAR V2.0 (USA)

## Environmental

Relative Humidity 0...95 %  
Storage Relative Humidity 0...95 %

## Ordering and shipping details

---

GTIN 731304424468

## Packing Units

---

Unit Type of Package 1 PCE

---

Number of Units in Package 1 1

## Offer Sustainability

---

REACH Regulation [REACH Declaration](#)

---

EU RoHS Directive Compliant  
[EU RoHS Declaration](#)

---

Mercury free Yes

---

China RoHS Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information.

---

RoHS exemption information [Yes](#)

---

WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

---

Warranty 3 Years

## Recommended replacement(s)