

4MP IP Bullet Camera with AI and Audio and **Visual Deterrent, NDAA Compliant**

O4BDD1M

2.8-12mm motorized lens, white housing















Features

- Captures up to 4MP @ 30fps real time
- Built-in speaker with preset and custom sounds provides
- Built-in high-power red and blue lights provides visual deterrence
- IR range: up to 164' (depending on scene reflection)
- True WDR operation
- Micro SD card slot (card not included)
- ONVIF Profile T Compliant

- IP66 Weather Resistance
- Built-in standard PoE (IEEE 802.3af)
- Line crossing with counting/Intrusion detection?
- Person/Vehicle detection
- Junction box included (works with NPT/BSP specifications)
- 5 year warranty
- NDAA Compliant**





Junction Box

Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS
Maximum Resolution	2592 x 1520 (4MP)
Field of View	Horizontal: 94.2°~ 29.8°, Vertical: 62.4°-17°, Diagonal: 102°-33.9°
Minimum Illumination	0.005lux @ F1.6(AGC ON); 0 lux @ IR ON
White Balance	Auto, Indoor, Outdoor, Manual
Compensation	True WDR (120dB), BLC, HLC
Day/Night	Smart IR
Electronic Shutter Speed	1s~1/100000s
DNR	3D DNR
Angle Adjustment	Pan: 0° ~ 360°; Tilt: 0° ~ 90°; Rotation: 0° ~ 360°

Video Specifications

Video Specifications		
Main Resolution	2592x1520, 2560x1440 2304x1296, 1920x1080, 1280x720, D1, CIF, 480×240 @ 30fps	
Substream	1280x720, D1, CIF @ 30fps	
Third Stream	D1, CIF, 480×240 @30fps	
Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG	
Bitrate Control	VBR, CBR (64Kbps ~ 8Mbps)	
Multiple Streaming	3 streams	
Video Settings	Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Day/Night mode, Exposure, Gain, Corridor Pattern, Image flip/mirror	

Client Specifications Web Browser Support

DC Application

PC Application	Secure Guara, AW2 and Secure Guara, CW2
Mobile	SecureGuard® Client, Speco Blue
Interfaces	
Ethernet	RJ45 Jack, 10/100 Mbps, PoE
Power	12VDC input jack
Audio	Built-in speaker, 3.5mm input
Card slot	MicroSD, up to 256GB (not included)
Alarm	1ch alarm in, 1ch alarm out

Sagura Guard® VAAS and Sagura Guard® CAAS

Network Specifications

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTP, HTTPS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication
User Access	Max. 10 simultaneous users Actual number of users may vary depending on bandwidth

Other Specifications

PoE	Standard (IEEE 802.3af)
Analytics	Motion detection, region entrance/exiting/intrusion detection (people/vehicle classification), line crossing detection (people/vehicle classification), video tampering detection, scene change detection.
Alarm Triggers	Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection
Alarm Events	FTP upload, email upload
Image Settings	Watermark, IP address filtering, video mask, heartbeat, illegal login lock, image distortion correction

Audio Specifications

	Audio Compression	G.711A / G.711U
	Audio Input	3.5mm input
	Audio Output	Built-in speaker

Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	12.0W (max)
Operating Temperature	-40°F - 140°F
Operating Humidity	less than 95% (non-condensing)
Unit Dimensions	8.57" (L) x 3.17" (W) x 3.16" (H)
Unit Weight	1.53 lb
Certifications	FCC. ONVIF Profile T





With compatible Speco Blue Recorder



PoE Injector

Reset







Google Chrome, Microsoft Edge, Internet Explorer, Apple Safari





















Power Supply



Corner Mount Pole Mount





Ceiling Mount

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 8/22/22









