

5MP IP Advanced Analytic Turret Camera with White Light Intensifier[®] and Junction Box, NDAA Compliant

FULL Color

O5LT1

2.8mm fixed lens, white housing

Features

- Captures up to 5MP @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- Full Color capture in Day and Night with white LED
- H.265/H.264/MJPEG compression supported
- White LED range: 98' (depending on scene reflection)
- True WDR operation
- Micro SD card slot up to 256GB (card not included)
- ONVIF Profile T Compliant

- IP67 compliant
- Face/People/Vehicle detection**
- Line crossing/Intrusion/Scene Change Detection**
- Built-in mic and 1 channel audio line-in
- UL-listed*
- 5 year warranty
- NDAA Compliant* * *



TRUE POE SLOT IP67

LINE crossing

Camera Specifications		
Image Sensor	Progressive scan 1/2.7" CMOS, 5MP	
Maximum Resolution	2592 (H) x 1944 (V)	
Field of View	94.8° (H), 78.4° (V), 107.3° (D)	
Minimum Illumination	0 lux @ F.1 (White LED on)	
Day/Night	White LED	
White Balance	Auto, Indoor, Outdoor, Manual	
Compensation	True WDR (120dB), BLC, HLC	
Electronic Shutter Speed	1 sec. ~ 1/100000 sec.	
DNR	3D DNR	

Video Specifications

Main Resolution 2592x1944/2592x1520/2560x1440/2304x1296 1980x1080/1280x720@30fps		
Sub Stream 1280x720 / D1 / CIF / 480x240 @ 30fps		
Compression	H.265, H.264 (HP/MP/BP), MJPEG	
Bitrate Control VBR, CBR (64Kbps ~ 8Mbps)		
Multiple Streaming 3 streams		

Network Specifications

•		
Protocols	UDP/IPv4/IPv6/DHCP/NTP/RTSP/PPPoE/DDNS/SMTP/FTP/SNMP/ 802.1x/UPnP/HTTP/HTTPS	
DDNS support	Speco DDNS (free of charge)	
Security	User ID & Password protection, IP/MAC address filtering, digest authentication	
User Access	Max. 10 simultaneous users, Actual number of users may vary depending on bandwidth	

Audio Specifications

Audio Codec	G.711A / G.711U
Mono Input	Built-in mic or 3.5mm audio in
Mono Output	No

Client Specifications


•	
Web Browser Support	Windows (Internet 8 and up) Google Chrome, Microsoft Edge, Apple Safari, Mozilla Firefox
PC Application	SecureGuard® VMS, SecureGuard® CMS
Mobile	SecureGuard® Client (iPhone® and Android $^{\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!$
Other Platforms	Apple TV, Amazon Fire TV

Interfaces		
Ethernet		10/100 Mbps
Power		DC jack
Microphone Input		3.5mm
Card Slot		MicroSD, up to 256GB (not included)
Alarm		No
Reset		Yes
System Specifications		
PoE	Standard (IEEE 802.3af)	
Analytics	Motion detection, Object abandoned/missing detection, region entrance/exiting/intrusion detection (people/vehicle classification), line crossing detection (people/vehicle classification), video tampering detection, scene change detection, face detection, face capture.	
Alarm Triggers	Analytics, SD card error	
Alarm Events	FTP upload, email upload	
Image Settings	Watermark, IP address filtering, video mask, password protection	
Operating & Unit Specifications		
Certifications		UL-listed

^{*}as of March 2023 **with compatible Speco recorder

^{***}Products are in compliance with NDAA Section 889 Part B Guidelines





ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/28/23

Apps available from the following:

Onvir* 800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

