

## HD Video Transceiver with Pigtail (Balun)

### TVIUTPPT



#### Features

- Send HD-TVI signal up to 656' (200M) over UTP cable.
- BNC male to screw terminal with 4" (10cm) mini coax cable for easy connection.
- Compact size allows mounting of multiple units behind multiplexers, Quads, DVRs, etc.
- Passive, No power required.
- Ideal for retrofits using existing UTP cable.
- Built in ESD, EFT (impulse noise), lightning (surge) and transient protection.
- Used in pairs (Sold individually).
- Sold individually but used in pairs. Could be used in conjunction with another TVIUTPPT, or with the non-pigtail model TVIUTP

#### Specifications

Video Input / Output Terminals ..... BNC Male 1Vp-p, 75 Ohms  
 Video On Put / Output Terminals ..... Terminal Block  
 Bandwidth..... 50Hz - 60MHz ( -3dB )  
 Transmission Distance ..... HD-TVI: 656' (200M)  
 ESD Protection ..... 30 KV(air) | 15 KV (contact) ; complaint IEC 61000-4-2  
 EFT Protection..... 40A(5/50ns) ; IEC 61000-4-4 compliant  
 Lighting Protection..... 2A (8/20µs) ; IEC 61000-4-5 compliant  
 Surge Protection Startup Time ..... < 1 nS  
 Operating Temperature..... 32° F - 131° F,  
 Storage Temperature/Humidity..... -4° F - 185° F / up to 95%  
 Dimensions..... 0.6" (W) x 2" (H) x 0.6" (L)  
 Weight ..... 0.64 oz.

**NDAA**  
COMPLIANT

\*Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/21/22

#### Also Available



**TVIUTP**  
HD Video  
Transceiver