

HD Video Transceiver

TVIUTP

Features

- Send HD-TVI signal up to 656' (200M) over UTP cable.
- BNC male to screw terminal for easy connection.
- Compact size allows mounting of multiple units behind multiplexers, Quads, DVRs, etc.
- Passive, No power required.
- Ideal for retrofits using existing UTP cable.
- Built in ESD, EFT (impulse noise), lightning (surge) and transient protection.
- Sold individually but used in pairs. Could be used in conjunction with another TVIUTP, or with the pigtail model **TVIUTPPT**.

**HD
TVI**



Sold Individually

Specifications

Video Input (BNC Connector).....	1
Video Input	1Vp-p, 75 Ohms
Cable	Twisted Pair CAT 5
Bandwidth.....	50Hz - 60MHz (-3dB)
Transmission Distance	HD-TVI: 656' (200M)
RJ-45 Output	Terminal
ESD Protection	30 KV(Air) 15 KV (Contact) ; IEC 61000-4-2 compliant
EFT Protection.....	40A(5/50ns) ; IEC 61000-4-4 compliant
Lighting Protection.....	2A (8/20µs) ; IEC 61000-4-5 compliant
Surge Protection Attack Time	< 1 nS
Operating Temperature.....	32° F - 131° F,
Storage Temperature/Humidity....	-4° F - 185° F / up to 95%
Dimensions.....	0.6" (W) x 2" (H) x 0.6" (L)
Weight	0.64 oz.

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/21/22

Also Available



TVIUTPPT
HD Video Transceiver
with Pigtail