

**VLT4DG** 2.8mm fixed lens, dark gray housing



## Features

- Supports up to 4MP @ 15FPS
- Built-in high powered IR LED's
- Digital Wide Dynamic Range
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- 5 year warranty



Shown with included paintable, snap-on Chameleon Cover™



Included Junction Box



Camera Specifications	
Image Sensor	1/2.7" 4MP CMOS
Resolution	2MP: TVI, AHD, CVI, CVBS 4MP: TVI, AHD, CVI
Minimum Illumination	Color: 1 lux, BW: 0.5 lux
S/N Ratio	52dB
WDR	D-WDR / On / Off
Day/Night	IR cut filter (Auto, Color, B/W, EXT)
Brightness	1-20
AGC	0-20
DNR	2D-DNR (1-16)
Mirror	Default / H / V / HV
Remote Control Interface	UTC
IR LED	6 high power LED's, 66ft.

Operating & Unit Specifications	
Power	12VDC (power supply not included)
Power Consumption	5W
Unit Dimensions	2.51" (W) x 2.75" (H) x 7.79" (D)

**NDAA COMPLIANT**

\*Products are in compliance with NDAA Section 889 Part B Guidelines

