

Portable CCTV Installation & Testing Monitor

VMS2

Features

- LCD display easily allows for checking the video signal of the CCTV camera being tested
- An audio jack tests the audio signal
- Built-in rechargeable battery has a life of 4 hours
- An LED light displays low battery level
- Visor blocks out sunglare on the LCD display
- The heavy duty casing, durable handle and shoulder belt (included) make this unit conveniently portable
- 1 year warranty



Specifications

Resolution.....	480 x 234
Brightness	350cd
Input Video Signal	1.0Vp-p (sync., negative) termination 75 Ohm
LCD Technology	TFT active matrix
Display Size	4"
Contrast Ration.....	250:1
View Angle.....	L/R ±45° U/D:10°/30°
Audio Input	30 mVp-p – 100 mVp-p
Audio Output.....	0.5W max
Charging Time	8 hours charging time, 4 hours operating time
Video/Audio Connector.....	RCA W/BNC plug adapter
Power Consumption	4.5W
Rechargeable Battery	12V.1.1AH
Power Supply	12VDC (power supply included)
Dimensions	6" (W) x 5.1" (H) x 3" (D)
Weight	4.3 lbs.
Extra battery available	BVMS2

NDA
COMPLIANT

*Products are in compliance with NDA Section 889 Part B Guidelines