

**WBM6T** 6.5", white housing, 70V/25V

**WBM6TA** 6.5", white housing, Built-in 10W amplifier

### Features

- Speaker is completely enclosed in a sturdy metal enclosure
- Design greatly reduces chance of damage to or tampering with speaker
- WBM6TA is ideal for surveillance audio applications



Speaker Specifications	WBM6T	WBM6TA
RMS Output Power	20W	
Max Output Power	40W	
Power	70V/25V Transformer	12VDC (not included-use PSW5)
Transformer Settings	6W, 3W, 1.5W	N/A
Sensitivity (1W/1M)	87dB	
Maximum SPL (Pmax/1M)	103dB	
Impedance	8 Ohms	
Magnet Material and Weight	Ferrite, 10 oz	
Frequency Response Range	110Hz - 20kHz	
Dispersion	180°	
Driver	6.5" polypropylene cone, rubber edge woofer, .5 PEI dome tweeter	
Amplifier	N/A	10W
Input	N/A	3.5mm

### Operating Specifications

Dimensions	7.7" (L) x 7.7" (W) x 3.2" (H)	
Speaker Weight	6 lbs	7 lbs
Speaker Body Material	Metal	
Speaker Grille Material	Metal	

**NDAA**  
COMPLIANT

\*Products are in compliance with NDAA Section 889 Part B Guidelines

### Optional Accessories



**PSW5**  
12VDC  
Power Supply