



# APC SYMMETRA LX FLAME RETARDANT BATTERY MODULE

SYBT5FR

Uν	er	VI	е	W	•
----	----	----	---	---	---

Presentation	Extended run power protection for servers, networks, and telecommunications
Lead time	Usually in Stock

#### Main

Number of rack unit	0U
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide

#### **Batteries & Runtime**

Battery Placement	Internal Battery
Battery blocks per string	10
Battery Slots Empty	0
Included Battery Modules	0
Battery manufacturer	Yuasa
Device mounting	Enclosed battery cartridge
Battery voltage	120 V
RBC Quantity	1

### **Physical**

Height	5.51 in (14 cm)
Width	8.27 in (21 cm)
Depth	21.50 in (54.6 cm)
Net Weight	64.15 lb(US) (29.1 kg)
Mounting Mode	Not rack-mountable

#### Conformance

Product Certifications	CSA
Standards	UL 1778

#### **Environmental**

Ambient Air Temperature for	32104 °F (040 °C)
Operation	
Operating altitude	010000 ft
Relative Humidity	095 %
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage altitude	015000 ft (0.004572.00 m)
Storage Relative Humidity	095 %

# Ordering and shipping details

**GTIN** 731304221623

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.16 in (38.5 cm)
Package 1 Width	29.53 in (75 cm)
Package 1 Length	11.26 in (28.6 cm)
Package 1 Weight	71.17 lb(US) (32.28 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Take-back	Take-back program available	

### **Contractual warranty**

Warranty 2 years repair or replace

Recommended replacement(s)