

Product data sheet

Specifications



Symmetra PX 500kW Bottom Feed Frame for 500kW Dual Mains Configs

SYBFF

Overview

Lead time Usually Ships within 6 Weeks

Main

Main Input Voltage 480 V 3 phase
400 V 3 phase

Battery Type External battery system

Provided Equipment User Manual

Physical

Color Black

Height 78.39 in (199.1 cm)

Width 11.81 in (30 cm)

Depth 42.13 in (107 cm)

Net Weight 330.69 lb(US) (150 kg)

Input

Number of input connectors 1 Hard Wire 4-wire (3PH + G)
1 Hard Wire 5-wire (3PH + N + G)

Conformance

Product Certifications cUL Listed
CE
UL Listed
VDE

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)

Operating altitude 0...3333 ft

Relative Humidity 0...95 %

Ambient Air Temperature for Storage 5...104 °F (-15...40 °C)

Storage altitude 0...50000 ft (0.00...15240.00 m)

Storage Relative Humidity 0...95 %

Ordering and shipping details

GTIN 731304256458

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.06 in (213.5 cm)
Package 1 Width	47.64 in (121 cm)
Package 1 Length	29.33 in (74.5 cm)
Package 1 Weight	410.85 lb(US) (186.36 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 1 year repair or replace

Recommended replacement(s)