

Product data sheet

Specifications



APC High Performance Battery Module for the Symmetra PX 250/500kW

SYBT9-B6

Overview

Lead time Usually in Stock

Main

Battery Type VRLA

Provided Equipment Installation guide

Batteries & Runtime

Battery Placement Internal Battery

Battery blocks per string 6

Battery Life 3...5 year(s)

Device mounting Enclosed battery cartridge

Battery Voltage 384 V

Battery Volt-Amp-Hour Capacity 5184 VAh

Physical

Height 6.26 in (15.9 cm)

Width 4.21 in (10.7 cm)

Depth 27.56 in (70 cm)

Net Weight 337.31 lb(US) (153 kg)

Conformance

Product Certifications cUL Listed
Eurobat General Purpose
UL Listed
VDE

Environmental

Ambient Air Temperature for Operation 64...81 °F (18...27 °C)

Operating altitude 0...3333 ft

Relative Humidity 0...95 %

Ambient Air Temperature for Storage 5...104 °F (-15...40 °C)

Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	731304569282
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.09 in (18 cm)
Package 1 Width	31.89 in (81 cm)
Package 1 Length	25.51 in (64.8 cm)
Package 1 Weight	354.75 lb(US) (160.91 kg)
Number of Units in Package 3	7

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Take-back	Take-back program available

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------

Recommended replacement(s)