

Product data sheet

Specifications



Symmetra PX 100 Maintenance Bypass Panel, 208V

SYMBP100F

Overview

Presentation	Installed next to the UPS for convenient access, the 300mm Maintenance Bypass Panel isolates the UPS from the critical load during service procedures.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phase
Main Output Voltage	208 V 3 phase

Physical

Color	Black
Height	78.90 in (200.4 cm)
Width	11.81 in (30 cm)
Depth	42.13 in (107 cm)
Net Weight	371.79 lb(US) (168.64 kg)
Mounting Location	Front
Mounting preference	No preference

Input

Input Frequency	60 Hz
Number of input connectors	1 Hard Wire 5-wire (3PH + N + G)

Conformance

Product Certifications	cUL Listed CSA
Standards	UL 1778

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft

Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	731304293927
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.65 in (215 cm)
Package 1 Width	47.64 in (121 cm)
Package 1 Length	33.39 in (84.8 cm)
Package 1 Weight	416.87 lb(US) (189.09 kg)
Number of Units in Package 3	1

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Take-back	Take-back program available

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------

Recommended replacement(s)