

# Product data sheet

Specifications



## APC Symmetra LX 4kVA scalable to 8kVA N+1 Rack-mount, 208/240V

SYA4K8RMP

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	208 V
Other Input Voltage	240 V
Main Output Voltage	120 V 208 V
Other Output Voltage	240 V
Kw Rating	3200 W
Rated power in VA	4000 VA
Output connection type	4 NEMA L5-20R 2 NEMA L14-30R
Output connector type	Hard Wire 4-wire (2PH+N+G) 1
Number of rack unit	13U
Battery type	Lead-Acid battery
Provided equipment	CD with software Documentation CD Installation guide User Manual Web/SNMP Management Card

### Batteries & Runtime

Included Battery Modules	1
Battery Slots Empty	1
Typical recharge time	3 h
Additional information	Configurable for 120/208 or 120/240 output voltage
Battery Charge Power (Watts)	287 W rated
Battery power in VAh	864 VAh runtime
Battery Life	3...5 year(s)
Replacement battery	<a href="#">SYA8K16PX798</a>
	<a href="#">SYBT5</a>
Battery option	SYBT5 1 1728 VAh SYARMXR3B3 1 3456 VAh SYARMXR3B3 2 6048 VAh SYARMXR9B9 1 8640 VAh

SYARMXR9B9 2 16416 VAh  
SYARMXR9B9 3 24192 VAh  
SYARMXR9B9 4 31968 VAh  
SYARMXR9B9 5 39744 VAh

---

Extendable Run Time	1
---------------------	---

## General

---

Product web sub-family	4kVA power increments
------------------------	-----------------------

---

Number of power module free slots	2
-----------------------------------	---

---

Number of power module filled slots	1
-------------------------------------	---

---

Redundant	Yes
-----------	-----

## Physical

---

Color	Black Silver
-------	-----------------

---

Height	22.52 in (57.2 cm)
--------	--------------------

---

Width	18.58 in (47.2 cm)
-------	--------------------

---

Depth	27.09 in (68.8 cm)
-------	--------------------

---

Net Weight	295.62 lb(US) (134.09 kg)
------------	---------------------------

---

Mounting Location	Front
-------------------	-------

---

Mounting preference	Lower
---------------------	-------

---

Mounting Mode	Rack-mounted
---------------	--------------

---

Two post mountable	0
--------------------	---

---

USB compatible	No
----------------	----

## Input

---

Input Frequency	45...65 Hz auto-sensing
-----------------	-------------------------

---

Number of input connectors	1 Hard Wire 4-wire (2PH+N+G)
----------------------------	------------------------------

---

Efficiency at full load	96...138 V line to neutral
-------------------------	----------------------------

---

Input Total Harmonic Distortion	Less than 7% for full load
---------------------------------	----------------------------

---

Input Power Factor at Full Load	0.98
---------------------------------	------

## Output

---

Max Configurable Power (Watts)	6400 W
--------------------------------	--------

---

Harmonic distortion	Less than 5 % at full load
---------------------	----------------------------

---

Output Frequency (sync to mains)	47...63 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal not synced 50 Hz +/- 0.1 % for 50 Hz nominal not synced
----------------------------------	--

---

Crest factor	Up to 5 : 1
--------------	-------------

---

Topology	Double Conversion Online
----------	--------------------------

---

Waveform Type	Sine wave
---------------	-----------

---

Bypass type	Internal Bypass (Automatic and Manual) Optional External Bypass
-------------	--

---

	90 % full load)
--	-----------------

---

Maximum output current	18 A
------------------------	------

---

Maximum configurable power in VA	8000 VA
----------------------------------	---------

## Conformance

Product Certifications	CSA
Standards	FCC Part 15 class A OSHPD UL 1778

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...15000 ft (0.00...4572.00 m)
Acoustic level	62 dBA
Heat dissipation	3707 Btu/h

## Communications & Management

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 2 with environmental monitoring
Control panel	Multi-function LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

## Ordering and shipping details

GTIN	731304619338
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.98 in (78.7 cm)
Package 1 Width	39.25 in (99.7 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	366.76 lb(US) (166.36 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Optimized Energy Efficiency	Energy efficient product

---

**Take-back** Take-back program available

## **Contractual warranty**

---

**Warranty** 2 years repair or replace

**Recommended replacement(s)**